

Neuromorphic vision and transfer learning for autonomous driving

Hajer Fradi

▶ To cite this version:

Hajer Fradi. Neuromorphic vision and transfer learning for autonomous driving. European Responsible Research and Innovation Event, Oct 2024, Rennes, France. hal-04739726

HAL Id: hal-04739726 https://imt-atlantique.hal.science/hal-04739726v1

Submitted on 16 Oct 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

NEUROMORPHIC VISION AND TRANSFER LEARNING FOR AUTONOMOUS DRIVING







NOETIC Project Hajer Fradi


hajer.fradi@imt-atlantique.fr




INTRODUCTION

Frame-based vision:

- More than 60 years, research has been focused on frame-based cameras.
- Some limitations:







Event-based vision:


- Novel sensor that measures motion in the scene.
- First introduced in 2008 as the Dynamic Vision Sensor.
- Low latency ($\sim 1 \,\mu s$).
- Free from motion blur.
- High dynamic range (140 dB compared to the usual 60 dB).
- Low power consumption.

CHALLENGES & MOTIVATION

Challenges:

Unconventional, asynchronous and sparse output of event-cameras

In view of the recency of event-cameras, the full potential of deep-learning is not yet full unlocked.




Computer Vision Datasets


Data from: https://homepages.inf.ed.ac.uk/rbf/CVonline/Imagedbase.htm

□ Research axes:


The complementarity of frame-based and event-based modalities through fusion schemes.



Transfer the knowledge from data-rich RGB (conventional frame-based) domain to data-scarce event-based domain



PROPOSED FUSION APPROACH



□ Step 1: Input event representation

- An important step that involves mapping event streams to event frames.
- Stacking based on the number of events [1].
- Opting for a multi-channel representation for highly detailed description.
- The number of channels and events is optimized by measuring the distortion between the raw events and their representations.

□ Step 2: Backbone network

- YOLOv7 [2] detector is chosen as a good compromise between accuracy and time complexity.
- YOLOv7 is updated and configured to support multi-channel inputs.

☐ Step 3: Very late fusion


- Very-late fusion through probabalistic ensembling derived from Bayes' rule [3].
- The class posteriors and bounding boxes from single-model detectors are probabilistically fused.

EXPERIMENTAL RESULTS

Datasets:

- DSEC-MOD [4] for detecting moving objects of 8 classes.
- PKU-DDD17 [5] for car detection in driving scenarios.
- SimCar: Synthetic data generated within a simulated drone navigation environment using AirSim and Unreal Engine, and v2e toolbox.

Qualitative results:



REFERENCES

- [1] Y. Nam, M. Mostafavi, K.-J. Yoon, and J. Choi. Stereo depth from events cameras: Concentrate and focus on the future. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 6114-6123, 2022.
- [2] C.-Y. Wang, A. Bochkovskiy, and H.-Y. M. Liao. Yolov7: Trainable bag-of-freebies sets new state-of-the-art for real-time object detectors. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 7464–7475, 2023.
- [3] Y.-T. Chen, J. Shi, Z. Ye, C. Mertz, D. Ramanan, and S. Kong. Multimodal object detection via probabilistic ensembling. In European Conference on Computer Vision, pages 139-158. Springer, 2022.
- [4] Z. Zhou, Z. Wu, R. Boutteau, F. Yang, C. Demonceaux, and D. Ginhac. Rgb-event fusion for moving object detection in autonomous driving. In 2023 IEEE International Conference on Robotics and Automation (ICRA), pages 7808-7815. IEEE, 2023.
- [5] J. Li, S. Dong, Z. Yu, Y. Tian, and T. Huang. Event-based vision enhanced: A joint detection framework in autonomous driving. In 2019 ieee international conference on multimedia and expo (icme), pages 540 1396–1401. IEEE, 2019.